

## Key Features

- HD 768p Resolution
- 10-point projected capacitive touch
- HDMI and VGA inputs
- Dual integrated speakers
- Durable, Scratch-resistant
   Screen



## Product **Description**

The ViewSonic TD1630-3 is a 16" (15.6" viewable) display with 10-point multi-touch functionality. With an advanced ergonomic design, the TD1630-3 can tilt or lay flat to give users maximum comfort. Delivering touchscreen versatility, this display offers fantastic flexibility for retail or business settings, while VGA and HDMI inputs provide ample connectivity. Compatibility with a wide range of operating systems, including Windows 10/11 and Linux versions\*, along with dual integrated speakers, make this intuitive touchscreen a highly accurate, ultra-responsive touch experience that is ideal for interactivity in a retail or business settings.

\*Supports Windows 7/8/10/11, Linux Kernel 4.X/3.X







- 1. Internal Speakers
- 2. USB
- 3. DC In 4. VESA Compatible(Wall Mount
- 75x75mm)
- 5. VGA 6. HDMI

7. Earphone

**Visit Us** 

www.viewsonic.com

**CONTROLS** 

	-	_		^	٠,
DI	5	μ	L.	А	Y

DISPLAY		CONTROLS		
Display Size (in.):	16	Physical Controls:	1, 2, Up, Down, Power	
Viewable Area (in.):	15.6		Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall	
Panel Type:	TN Technology			
Resolution:	1366 x 768	On Screen Display:		
Resolution Type:	WXGA (Wide XGA)			
Static Contrast Ratio:	500:1 (typ)	OPERATING CONDITIONS	•	
Dynamic Contrast Ratio:	10M:1		32°F to 104°F (0°C to	
Light Source:	LED	Temperature:	40°C)	
Brightness:	190 cd/m² (typ)	Humidity (non-condensing):	20% to 90%	
Colors:	262K	WALL MOUNT		
Color Space Support:	6 bit true	VESA Compatible:	75 x 75 mm	
Aspect Ratio:	16:9	INPUT SIGNAL		
Response Time (Typical Tr+Tf):	12ms	Frequency Horizontal:	30 ~ 61KHz	
,	90° horizontal, 60°	Frequency Vertical:	56 ~ 75Hz	
Viewing Angles:	vertical	VIDEO INPUT		
Backlight Life (Hours):	15000 Hrs (Min)	Digital Sync:	TMDS - HDMI (v1.4)	
Curvature:	Flat	Analog Sync:	Separate - RGB Analog	
Refresh Rate (Hz):	60	ERGONOMICS		
Blue Light Filter:	Yes	Tilt (Forward/Back):	15° / 50°	
Color Gamut:	NTSC: 45% size (Typ)	WEIGHT (IMPERIAL)		
Goldi Gainat.	sRGB: 67% size (Typ)	Net (lbs):	2.9	
Pixel Pitch:	0.252 mm (H) x 0.252 mm (V)	Net Without Stand (lbs):	2.9	
Touch Coroon	Projected Capacitive, 10-	Gross (lbs):	5.5	
Touch Screen:	point multi-touch	WEIGHT (METRIC)		
Surface Treatment:	Glossy, Hard Coating (7H)	Net (kg):	1.3	
Cover Glass Thickness:	0.83mm	Net Without Stand (kg):	1.3	
COMPATIBILITY	0.00111111	Gross (kg):	2.5	
PC Resolution (max):	1366x768	DIMENSIONS (IMPERIAL) (WX	(HXD)	
Mac® Resolution (max):	1366x768	Packaging (in.):	17.8 x 15.3 x 3.4	
made resolution (max).	Windows 7/8/8,1/10/11	Physical (in.):	14.9 x 9.7 x 1.5	
PC Operating System:	certified; macOS tested	Physical Without Stand (in.):	14.9 x 9.7 x 1.5	
Mac® Resolution (min): 1366x768  CONNECTOR		DIMENSIONS (METRIC) (WXHXD)		
		Packaging (mm):	453 x 389 x 86	
VGA:	1	Physical (mm):	379 x 247 x 37	
USB 2.0 Type B:	1	Physical Without Stand (mm):	379 x 247 x 37	
3.5mm Audio In:	1	GENERAL		
HDMI 1.4:	1		CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, RCM, GEMS, BIS	
Power in:	DC Socket (Center Positive)	Regulations:		
AUDIO	,		TD1630-3 x1, 3-pin Plug	
Internal Speakers:	1Watts x2		(IEC C13 / CEE22) x1, VGA Cable (Male-Male)	
POWER		PACKAGE CONTENTS:	x1, USB A/B Cable (v2.0; Male-Male) x1, Audio	
Eco Mode (Conserve):	4.3W		Cable (Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1	
Eco Mode (optimized):	4.9W			
Consumption (typical):	5.5W	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.	
Consumption (max):	6W	1.00yolo/Disposal.		
Voltage:	AC 100-240V	Warranty:	*Warranty offered may differ from market to	

Stand-by: 0.5W

Kensington Lock Slot:

Power Supply:	External Power Adaptor
ADDITIONAL HARDWARE	

1

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.