

## Key Features

- SuperClear® IPS panel
- Full HD 1080p resolution
- 100Hz Variable Refresh rate delivers fluid visuals
- 1ms (MPRT) response time for precision
- Eye-care technology for comfortable viewing



## Product **Description**

The ViewSonic VA2209-H is a 22" Full HD monitor featuring HDMI and VGA inputs for business and home use. The optimal screen performance and comfortable viewing without tearing or stuttering is delivered through Variable Refresh Rate, eye-care technology, and various ViewMode presets. Experience truly seamless multitasking on just one screen with a VESA-compatible mount at low power consumption.



- 1. HDMI
- 2. VGA
- 3. Audio Out
- 4. Power In
- 5. VESA Compatible(Wall Mount 100 x 100mm)

**Visit Us** 

www.viewsonic.com

D	ıς	P	L.	Δ	γ

DISPLAY		C	
Display Size (in.):	22		
Viewable Area (in.):	21.5		
Panel Type:	IPS Technology		
Resolution:	1920 x 1080	٧	
Resolution Type:	FHD (Full HD)		
Static Contrast Ratio:	1,000:1 (typ)		
Dynamic Contrast Ratio:	50M:1		
Light Source:	LED		
Brightness:	250 cd/m² (typ)		
Colors:	16.7M	٧	
Color Space Support:	8 bit (6 bit + FRC)		
Aspect Ratio:	16:9		
Response Time (MPRT):	1ms	E	
Viewing Angles:	178º horizontal, 178º vertical	V	
Backlight Life (Hours):	30000 Hrs (Min)		
Curvature:	Flat		
Refresh Rate (Hz):	100		
Variable Refresh Rate Technology:	Yes	٧	
Blue Light Filter:	Yes		
Flicker-Free:	Yes		
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)	C	
Pixel Pitch:	0.249 mm (H) x 0.241 mm (V)		
Surface Treatment:	Anti-Glare, Hard Coating (3H)		
COMPATIBILITY		L	
PC Resolution (max):	1920x1080		
Mac® Resolution (max):	1920x1080	i	
PC Operating System:	Windows 10/11 certified; macOS tested	G	
Mac® Resolution (min):	1920x1080		
CONNECTOR		ď	
VGA:	1		
3.5mm Audio Out:	1		
HDMI 1.4:	1		
Power in:	DC Socket (Center Positive)		
POWER			
Eco Mode (Conserve):	16W		
Eco Mode (optimized):	18W		
Consumption (typical):	20W		
Consumption (max):	22W		
Voltage:	AC 100-240V		
Stand-by:	0.3W		
Power Supply:	External Power Adaptor		
ADDITIONAL HARDWARE			

onitor with Fast 1ms Respo	onse Time - Datasheet - ViewSonic भारत, Iı TIONS				
Temperature:	32°F to 104°F (0°C to 40°C)				
Humidity (non-condens	sing): 20% to 90%				
WALL MOUNT					
VESA Compatible:	100 x 100 mm				
INPUT SIGNAL					
Frequency Horizontal:	RGB Analog: 24 ~ 86KHz, HDMI (v1.4): 30 ~ 115KHz				
Frequency Vertical:	RGB Analog: 48 ~ 75Hz, HDMI (v1.4): 48 ~ 100Hz				
VIDEO INPUT					
Digital Sync:	TMDS - HDMI (v1.4)				
Analog Sync:	Separate - RGB Analog				
ERGONOMICS					
Tilt (Forward/Back):	-3° / 20°				
WEIGHT (IMPERIAL)					
Net (lbs):	5.1				
Net Without Stand (lbs	9): 4.2				
Gross (lbs):	7.3				
WEIGHT (METRIC)					
Net (kg):	2.3				
Net Without Stand (kg)	): 1.9				
Gross (kg):	3.3				
DIMENSIONS (IMPE	RIAL) (WXHXD)				
Packaging (in.):	21.5 x 15.6 x 4.7				
Physical (in.):	19.3 x 15 x 7.4				
Physical Without Stand	d (in.): 19.3 x 11.5 x 1.6				
DIMENSIONS (METR	RIC) (WXHXD)				
Packaging (mm):	545 x 395 x 120				
Physical (mm):	491 x 381 x 189				
Physical Without Stand	d (mm): 491 x 291 x 39				
GENERAL					
Regulations:	RoHS, WEEE, BSMI, TGM, BIS				
PACKAGE CONTENTS	VA2209-H x1, HDMI Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1				
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.				
Warranty:	*Warranty offered may differ from market to market				
l I					

## **ADDITIONAL HARDWARE**

Kensington Lock Slot:

CONTROLS

Physical Controls:

Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)

Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.