

# ViewSonic® LCD DISPLAY VG2409-MHU

## Key Features

- SuperClear® IPS panel
- HDMI, VGA, and USB-C 3.2 inputs for simple connectivity and 65W power delivery
- Super narrow bezel with dual 2W speakers
- Ergonomic tilt, swivel, pivot and height adjustment capabilities
- 75Hz Refresh rate delivers fluid visuals



## Product Description

The ViewSonic VG2409-MHU is a 24" Full HD monitor featuring HDMI, VGA and USB-C inputs for business and home use. Simplify your work with just one cable that provides audio and video, 65W power transfer. The variable refresh rate, eye-care technology, and various ViewMode presets cater for optimal screen performance and comfortable viewing without tearing or stuttering. Expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at low energy consumption.



1. Menu Control Panel
2. VESA Compatible(Wall Mount 100 x 100mm)
3. AC In
4. USB-C
5. HDMI
6. VGA

7. Audio Out
8. Speaker

Visit Us

[www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

Display Size (in.):	24
Viewable Area (in.):	23.6
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	250 cd/m <sup>2</sup> (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	75
Variable Refresh Rate Technology:	Yes
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.272 mm (H) x 0.272 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

**COMPATIBILITY**

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080

**CONNECTOR**

VGA:	1
USB 3.2 Type C DisplayPort Alt mode only :	1 (65W power charger)
3.5mm Audio Out:	1
HDMI 1.4:	1
Power in:	DC Socket (Center Positive)

**AUDIO**

Internal Speakers:	2Watts x2
--------------------	-----------

**POWER**

Eco Mode (Conserve):	10W
Eco Mode (optimized):	12W
Consumption (typical):	18W

**CONTROLS**

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

**WALL MOUNT**

VESA Compatible:	100 x 100 mm
------------------	--------------

**INPUT SIGNAL**

Frequency Horizontal:	24 ~ 86KHz
Frequency Vertical:	48 ~ 75Hz

**VIDEO INPUT**

Digital Sync:	TMDS - HDMI (v1.4), Micro-Packet - Type C
Analog Sync:	Separate - RGB Analog

**ERGONOMICS**

Height Adjust (mm):	130
Swivel:	360°
Tilt (Forward/Back):	-3.5° / 28°
Pivot (Right/Left):	90° / 90°

**WEIGHT (IMPERIAL)**

Net (lbs):	10.4
Net Without Stand (lbs):	5.9
Gross (lbs):	14.7

**WEIGHT (METRIC)**

Net (kg):	4.7
Net Without Stand (kg):	2.7
Gross (kg):	6.7

**DIMENSIONS (IMPERIAL) (WXHXD)**

Packaging (in.):	24.5 x 20.5 x 5.7
Physical (in.):	21 x 15.03~20.15 x 9.2
Physical Without Stand (in.):	21 x 12.6 x 2.1

**DIMENSIONS (METRIC) (WXHXD)**

Packaging (mm):	622 x 520 x 144
Physical (mm):	534 x 381.8~511.8 x 233
Physical Without Stand (mm):	534 x 321 x 54

**GENERAL**

Regulations:	RoHS, WEEE, BIS
PACKAGE CONTENTS:	VG2409-MHU x1, 3-pin Mickey Mouse Plug (IEC C5) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.

Consumption (max):	19W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

Warranty:

\*Warranty offered may differ from market to market

**ADDITIONAL HARDWARE**

Kensington Lock Slot:	1
-----------------------	---

Cable Organization: Yes  
Copyright © ViewSonic Corporation 2000-2024. All rights reserved.