

Key Features

- vDisplay Manager (free download)
- Narrow bezel
- HDMI, DisplayPort and VGA inputs
- SuperClear® IPS technology
- Versatile stand design



Product **Description**

ViewSonic VG2448 is a 24" (23.8" viewable) 1080p monitor with productivity enhancing features including IPS technology and an advanced ergonomic design for the modern day office. Utilising SuperClear® IPS technology and 1080p resolution, VG2448 delivers a crisp, clear image from any viewing angle. An advanced ergonomic design offers the widest range of customisable adjustments currently available to provide maximum comfort, including dual direction pivot, swivel, height adjustment, and an impressive 40° tilt, which enables you to use the monitor while standing and to have strategic group discussions around the screen. VG2448 uses environmentally friendly packaging and offers quick and easy out-of-the-box set-up via the Quick Release stand. The cloud client mountable stand coupled with cable management design features, makes VG2448 perfect for deployment in cloud-based environments. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB 3.2 inputs.







- 1. VESA Compatible(Wall mount 100mm x
- Menu Control Panel
 USB down stream x 2
- 4 AC In
- 6. HDMI

- 7. VGA 8. USB up stream

Visit Us

www.viewsonic.com

DISPLAY		CONTROLS	
Display Size (in.):	24		Key 1 (eye), Key 2, Key 3, Key 4, Ke
Viewable Area (in.):	23.8	Physical Controls:	5, Key 6 (power)
Panel Type:	IPS Technology	On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual
Resolution:	1920 x 1080	OPERATING CONDITIONS	Image Adjust, Setup Menu
Resolution Type:	FHD (Full HD)		32°F to 104°F (0°C to 40°C)
Static Contrast Ratio:	1,000:1 (typ)	Temperature:	
Dynamic Contrast Ratio:	50M:1	Humidity (non-condensing):	20% to 90%
Light Source:	LED	WALL MOUNT	100 x 100 mm
Brightness:	250 cd/m² (typ)	VESA Compatible: INPUT SIGNAL	100 X 100 IIIIII
Colors:	16.7M	Frequency Horizontal:	24 ~ 82KHz
Color Space Support:	8 bit (6 bit + Hi-FRC)		50 ~ 75Hz
Aspect Ratio:	16:9	Frequency Vertical:	50 ~ 75HZ
Response Time (Typical GTG):	5ms	VIDEO INPUT	TMDS - HDMI (v1.4), PCI-E -
Response Time (GTG w/OD):	5ms	Digital Sync:	DisplayPort (v1.2)
Viewing Angles:	178° horizontal, 178° vertical	Analog Sync:	Separate/Composite/SOG - RGB
Backlight Life (Hours):	30000 Hrs (Min)		Analog
Curvature:	Flat	ERGONOMICS	
		Height Adjust (mm):	130
Refresh Rate (Hz):	60	Swivel:	120°
Blue Light Filter:	Yes	Tilt (Forward/Back):	-5° / 40°
Flicker-Free:	Yes	Pivot (Right/Left):	90° / 90°
Color Gamut:	Adobe RGB: 77% size / 72% coverage (Typ) NTSC: 72% size (Typ) sRGB: 103% size / 92% coverage (Typ)	WEIGHT (IMPERIAL)	
		Net (lbs):	12.8
Pixel Pitch:	0.275 mm (H) x 0.275 mm (V)	Net Without Stand (lbs):	7.6
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Gross (lbs):	19.2
COMPATIBILITY	, mara dodding (dil)	WEIGHT (METRIC)	
PC Resolution (max):	1920x1080	Net (kg):	5.8
Mac® Resolution (max):	1920×1080	Net Without Stand (kg):	3.4
wace resolution (max).	Windows 7/8/8.1/10/11 certified;	Gross (kg):	8.7
PC Operating System:	macOS tested	DIMENSIONS (IMPERIAL) (WXHXD)	
Mac® Resolution (min):	1920x1080	Packaging (in.):	23.8 x 15.2 x 8.3
CONNECTOR		Physical (in.):	21.6 x 15.24~20.37 x 8
VGA:	1	Physical Without Stand (in.):	21.6 x 12.8 x 2
USB 3.2 Type A Down Stream:	4	DIMENSIONS (METRIC) (WX	HXD)
USB 3.2 Type B Up Stream:	1	Packaging (mm):	604 x 385 x 210
HDMI 1.4:	1	Physical (mm):	549 x 387.03~517.03 x 202
DisplayPort:	1	Physical Without Stand (mm):	549 x 326 x 50
Power in:	3-pin Socket (IEC C14 / CEE22)	GENERAL	
AUDIO			cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, GS, UKCA, BSMI, TGM RCM, GEMS, VCCI, PSE, BIS, CCC China RoHS, China Energy Label
Internal Speakers:	2Watts x2	Regulations:	
POWER			
Eco Mode (Conserve):	14.62W		
Eco Mode (optimized):	17.42W	PACKAGE CONTENTS:	VG2448 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2 Male-Male) x1, USB A/B Cable (v3.2 Male-Male) x1, Quick Start Guide x1
Consumption (typical):	20.82W		
Consumption (max):	25W		
Voltage:	AC 100-240V	Recycle/Disposal:	Please dispose of in accordance wit
Stand-by:	0.5W	,	local, state or federal laws.
Power Supply:	Internal Power Supply	Warranty:	*Warranty offered may differ from market to market
ADDITIONAL HARDWARE	internal Fower Supply	Power Management:	Energy Star standards, EPEAT
Kensington Lock Slot:	1		
Renangion Lock Slot.			

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.

Cable Organization:

Yes