

Key Features

- **OLED TECH :** True Black with 1.07 Billion colors (10Bit)
- Real and Surreal: 100 % DCI-P3
 Pantone Validated color coverage
 with Delta E < 2 as color quality</p>
 guarantee
- Create Anywhere You Want:
 Tripod ready and foldable stand for outdoor shooting and indoor review
- Instant View: Camera ready (Micro HDMI) and USB-C charging that brings your creative workstation wherever you are
- Integrated hood: Foldaway hood attaches instantly when you need to eliminate ambient light



Product **Description**

Introducing industry-leading VP16-OLED with 1.07 Billion colors (10Bit). Merging what's real with the surreal, it boasts 100 % DCI-P3 Pantone Validated color coverage with Delta E < 2 as the color quality guarantee. Tripod-ready, VP16-OLED comes equipped with a foldable stand allowing you to perform your best in both indoor and outdoor settings. "Go dark" at any moment with a foldaway attachable hood that instantly eliminates any ambient light. Take your creative workstation no matter where you go and review the immediate results of your work, connecting your camera to the VP16-OLED via Micro HDMI and charging it effortlessly through USB-C connectivity.

Visit Us

www.viewsonic.com

1 101	Viewedille VI To deed To.o	O CEED I GRADIC MOINTOI DATASING	Viewoonie Globai
DISPLAY		CONTROLS	
Display Size (in.):	16	Physical Controls:	Up, Down, Left/Return, Right/Confirmed, Power
Viewable Area (in.):	15.6	Ir On Screen Display: V	Input Select, Color Mode,
Panel Type:	OLED Technology		ViewMode, Audio Adjust, Setup Menu
Resolution:	1920 x 1080	OPERATING CONDITIONS	Octop Menu
Resolution Type:	FHD (Full HD)		32°F to 104°F (0°C to
Static Contrast Ratio:	100,000:1 (typ)	Temperature:	40°C)
Dynamic Contrast Ratio:	20M:1	Humidity (non-condensing):	20% to 90%
Brightness:	400 cd/m² (typ)	INPUT SIGNAL	
Colors:	1.07B	Frequency Horizontal:	24 ~ 83KHz
Color Space Support:	10 bit (8 bit + FRC)	Frequency Vertical:	50 ~ 61Hz
Aspect Ratio:	16:9	VIDEO INPUT	
Response Time (Typical Tr+Tf):	1ms	Digital Sync:	TMDS - micro HDMI (v1.4), Micro-Packet -
Viewing Angles:	170° horizontal, 170° vertical	FREENOMICS	Type C
Backlight Life (Hours):	N/A Hrs (Min)	ERGONOMICS	000 / 000
Curvature:	Flat	Tilt (Forward/Back):	-60° / 20°
Refresh Rate (Hz):	60	WEIGHT (IMPERIAL)	2,2
Blue Light Filter:	Yes	Net (lbs):	
Dido Ligita inton	Adobe RGB: 112% size /	Net Without Stand (lbs):	2.2
	96% coverage (Typ) DCI- P3: 111% size / 100%	Gross (lbs):	4.8
	coverage (Typ) EBU:	WEIGHT (METRIC) Net (kg):	0.98
	149% size / 100% coverage (Typ) REC709: 150% size / 100% coverage (Typ) SMPTE-C: 163% size / 100% coverage (Typ) NTSC: 107% size (Typ) RGB: 150% size / 100%	, -,	
Color Gamut:		Net Without Stand (kg):	0.98
		Gross (kg): 2.2	
		DIMENSIONS (IMPERIAL) (WX	
	coverage (Typ)	Packaging (in.):	16.3 x 12.3 x 3.5
Pixel Size:	0.179 mm (H) x 0.179 mm (V)	Physical (in.):	14.1 x 8.92~12.38 x 0.8
	Glare, Hard Coating	Physical Without Stand (in.):	14.1 x 8.9 x 0.2
Surface Treatment:	(N/A)	DIMENSIONS (METRIC) (WXH Packaging (mm):	ХО) 415 x 312 x 90
COMPATIBILITY		Packaging (min).	
PC Resolution (max):	1920x1080	Physical (mm):	359 x 226.682~314.48 x 19
Mac® Resolution (max):	1920x1080	Physical Without Stand (mm):	359 x 227 x 6
PC Operating System:	Windows 10/11 certified; macOS tested	GENERAL	
Mac® Resolution (min):	1920x1080		cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NRCan, NOM, Mexico Energy, CE, CE EMC, CB, ROHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, RCM, GEMS, BIS
CONNECTOR			
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	2 (40W power charger)	Regulations:	
3.5mm Audio Out:	1		
Micro HDMI 1.4 In:	1	PACKAGE CONTENTS:	VP16-OLED x1, micro HDMI Cable (v1.4; Male- Male) x1, USB Type-C Cable (Male-Male) x1, USB Type-C to Type-A 3.2 Gen1 Cable (Male- Male) x1, AC/DC Adapter
Power in:	USB Type C (with video & data)		
AUDIO			
Internal Speakers:	1Watts x2		x1, Quick Start Guide x1, Hood x1
POWER			Please dispose of in
Eco Mode (Conserve):	5W	Recycle/Disposal:	accordance with local, state or federal laws.
Eco Mode (optimized):	6W		
Consumption (typical):	7W	Warranty:	*Warranty offered may differ from market to market

Consumption (max):	15W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

Power Management: Energy Star standards, EPEAT

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.