

Key Features

- Lifelike True Beauty: International color standard Pantone validated and 100% sRGB wide color gamut
- Precise Color: ColorPro Verified with factory pre-calibration for overwhelmed Delta E<2 color
- Multimedia Devices: Support USB-C with 60W high-speed charging, plus HDMI 1.4, DisplayPort 1.2, USB 3.2
- Unlimited Flexibility: Auto Pivot &
 Ergonomic Stand with tilt, swivel, pivot and
 height adjustments
- The Visible Difference: FHD (1920*1080) resolution IPS panel with 24" frameless design



Product **Description**

Designed with creative professionals in mind, the ViewSonic VP2456 delivers stunning true-to-life colors on screen. Pantone validated 100% sRGB coverage provides precise color reproduction, ensuring your work looks how it should, every time. A USB-C port that easily connects with your devices for easy charging and data transfer. Ergonomic engineering gives you the flexibility to do more without injury, while Auto Pivot lets shift between horizontal and vertical orientations effortlessly, letting your work be viewed how it's supposed to be.

Visit Us

www.viewsonic.com

	ADDITIONAL HARDWARE	
24	Kensington Lock Slot:	1
23.8	Cable Organization:	Yes
IPS Technology	CONTROLS	
1920 x 1080	Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)
FHD (Full HD)		Input Select, Audio Adjust,
1,000:1 (typ)	On Screen Display:	ViewMode, Color Adjust, Manual
20M:1	ODERATING CONDITIONS	Image Adjust, Setup Menu
LED		32°F to 104°F (0°C to 40°C)
250 cd/m² (typ)	·	20% to 90%
16.7M		20 / 10 30 / 1
8 bit (6 bit + FRC)		100 x 100 mm
16:9		, , , , , , , , , , , , , , , , , , , ,
5ms		30 ~ 83KHz
5ms		48 ~ 75Hz
178° horizontal, 178° vertical		
30000 Hrs (Min)		TMDS - HDMI (v1.4), PCI-E -
Flat	Digital Sync:	DisplayPort (v1.2), Micro-Packet - Type C
60	ERGONOMICS	.7.5 9
V		130
res		120°
Yes		-5° / 21°
Yes		90° / 90°
Adobe RGB: 80% size / 78%		
80% coverage (Typ) EBU: 107% size		14.4
size / 100% coverage (Typ) SMPTE-		8.9
NTSC: 77% size (Typ) sRGB: 108%		18.5
	·	6.5
Anti-Glare, Hard Coating (3H)		4
10001000	Gross (kg):	8.4
	DIMENSIONS (IMPERIAL) (W	XHXD)
	Packaging (in.):	24.4 x 15.4 x 9
tested tested, macOS	Physical (in.):	21.2 x 15.29~20.41 x 8.5
1920×1080	Physical Without Stand (in.):	21.2 x 12.6 x 2
		Z1.Z X 1Z.O X Z
	DIMENSIONS (METRIC) (WXI	
3	DIMENSIONS (METRIC) (WXI Packaging (mm):	
3		HXD)
1	Packaging (mm):	HXD) 620 x 392 x 228
1 1 (60W power charger)	Packaging (mm): Physical (mm):	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215
1 1 (60W power charger)	Packaging (mm): Physical (mm): Physical Without Stand (mm):	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 cTUVus, FCC-B, ICES003, Energy
1 1 (60W power charger) 1	Packaging (mm): Physical (mm): Physical Without Stand (mm):	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS,
1 1 (60W power charger)	Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 ctuvus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico
1 1 (60W power charger) 1 1 3-pin Socket (IEC C14 / CEE22)	Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, ROHS, ErP, REACH, WEEE, EAC,
1 1 (60W power charger) 1	Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL Regulations:	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, ROHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, VCCI, PSE, BIS VP2456 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-
1 1 (60W power charger) 1 1 3-pin Socket (IEC C14 / CEE22) 2Watts x2	Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, ROHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, VCCI, PSE, BIS VP2456 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male
1 1 (60W power charger) 1 1 3-pin Socket (IEC C14 / CEE22) 2Watts x2 11.6W	Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL Regulations: PACKAGE CONTENTS:	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 CTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, ROHS, EPP, REACH, WEEE, EAC, UkrSEPRO, BSMI, VCCI, PSE, BIS VP2456 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male Male) x1, Quick Start Guide x1
1 1 (60W power charger) 1 1 3-pin Socket (IEC C14 / CEE22) 2Watts x2 11.6W 13.6W	Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL Regulations:	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 CTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, ROHS, EPP, REACH, WEEE, EAC, UkrSEPRO, BSMI, VCCI, PSE, BIS VP2456 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male Male) x1, Quick Start Guide x1
1 1 (60W power charger) 1 1 3-pin Socket (IEC C14 / CEE22) 2Watts x2 11.6W 13.6W	Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL Regulations: PACKAGE CONTENTS: Recycle/Disposal:	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 CTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, ROHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, VCCI, PSE, BIS VP2456 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, USB Type-C Cable (Male- Male) x1, USB A/B Cable (v3.2; Male Male) x1, USB A/B Cable (v3.2; Male Male) x1, Usin A/B Cable (v3.2; Male Male (v3.
1 1 (60W power charger) 1 1 3-pin Socket (IEC C14 / CEE22) 2Watts x2 11.6W 13.6W 16W 27.5W	Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL Regulations: PACKAGE CONTENTS: Recycle/Disposal: Warranty:	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 CTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, ROHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, VCCI, PSE, BIS VP2456 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB Type-C Cable (Male-Male) x1, Quick Start Guide x1 Please dispose of in accordance with local, state or federal laws. *Warranty offered may differ from market to market
1 1 (60W power charger) 1 1 3-pin Socket (IEC C14 / CEE22) 2Watts x2 11.6W 13.6W 16W 27.5W AC 100-240V	Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL Regulations: PACKAGE CONTENTS: Recycle/Disposal:	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 CTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, VCCI, PSE, BIS VP2456 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, USB Type-C Cable (Male- Male) x1, USB A/B Cable (v3.2; Male Male) x1, USB A/B Cable (v3.2; Male Male) x1, Usin A/B
1 1 (60W power charger) 1 1 3-pin Socket (IEC C14 / CEE22) 2Watts x2 11.6W 13.6W 16W 27.5W	Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL Regulations: PACKAGE CONTENTS: Recycle/Disposal: Warranty:	HXD) 620 x 392 x 228 539 x 388.46~518.46 x 215 539 x 320 x 52 CTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, ROHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, VCCI, PSE, BIS VP2456 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB Type-C Cable (Male-Male) x1, Quick Start Guide x1 Please dispose of in accordance with local, state or federal laws. *Warranty offered may differ from market to market
	23.8 IPS Technology 1920 x 1080 FHD (Full HD) 1,000:1 (typ) 20M:1 LED 250 cd/m² (typ) 16.7M 8 bit (6 bit + FRC) 16:9 5ms 5ms 178° horizontal, 178° vertical 30000 Hrs (Min) Flat 60 Yes Yes Adobe RGB: 80% size / 78% coverage (Typ) DCI-P3: 80% size / 80% coverage (Typ) EBU: 107% size / 99% coverage (Typ) EBU: 107% size / 99% coverage (Typ) SMPTE-C: 117% size / 100% coverage (Typ) NTSC: 77% size (Typ) sRGB: 108% size / 100% coverage (Typ) 0.275 mm (H) x 0.275 mm (V) Anti-Glare, Hard Coating (3H) 1920x1080 Windows 10/11 certified; macOS tested	24

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.