

# ViewSonic® LCD DISPLAY

# VX2776-SH

## Key Features

- SuperClear® IPS panel for vivid picture quality and wider viewing angles
- Frameless bezel and stylish stand
- 75Hz Refresh Rate delivers fluid visuals
- Flexible connectivity with VGA and two HDMI ports
- User-customized and pre-calibrated ViewMode for every scenario



## Product Description

Whether for office use or for enjoying entertainment at home, the ViewSonic® VX2776-SH is designed to take your viewing experience to another level. With a SuperClear® IPS panel and a sleek frameless design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. The Full HD resolution boosts efficiency and image detail needed for work or play. A mega dynamic contrast ratio of 80M:1 delivers enhanced image depth for a better user experience. The Built-in HDMI and VGA inputs deliver flexible connectivity options for a wide range of devices.

**Visit Us** [www.viewsonic.com](http://www.viewsonic.com)

**DISPLAY**

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	250 cd/m <sup>2</sup> (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + Hi-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	75
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 100% size (Typ)
Pixel Pitch:	0.311 mm (H) x 0.311 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

**COMPATIBILITY**

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080

**CONNECTOR**

VGA:	1
3.5mm Audio Out:	1
HDMI 1.4:	2
Power in:	3-pin Socket (IEC C14 / CEE22)

**POWER**

Eco Mode (Conserve):	18W
Eco Mode (optimized):	21W
Consumption (typical):	24W
Consumption (max):	25W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

**ADDITIONAL HARDWARE**

Kensington Lock Slot:	1
-----------------------	---

**CONTROLS****OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

**WALL MOUNT**

VESA Compatible:	75 x 75 mm
------------------	------------

**INPUT SIGNAL**

Frequency Horizontal:	15 ~ 83KHz
Frequency Vertical:	50 ~ 75Hz

**VIDEO INPUT**

Digital Sync:	TMDS - HDMI (v1.4)
Analog Sync:	Separate - RGB Analog

**ERGONOMICS**

Tilt (Forward/Back):	-3° / 15°
----------------------	-----------

**WEIGHT (IMPERIAL)**

Net (lbs):	8.8
Net Without Stand (lbs):	7.9
Gross (lbs):	12.1

**WEIGHT (METRIC)**

Net (kg):	4
Net Without Stand (kg):	3.6
Gross (kg):	5.5

**DIMENSIONS (IMPERIAL) (WXHXD)**

Packaging (in.):	27.6 x 18.2 x 4.4
Physical (in.):	24.2 x 17.5 x 7.2
Physical Without Stand (in.):	24.2 x 14.1 x 1.9

**DIMENSIONS (METRIC) (WXHXD)**

Packaging (mm):	702 x 462 x 112
Physical (mm):	614 x 443 x 184
Physical Without Stand (mm):	614 x 357 x 49

**GENERAL**

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BSMI, BIS
--------------	--

PACKAGE CONTENTS:	VX2776-SH x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, Quick Start Guide x1
-------------------	--

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
-------------------	--

Warranty:	*Warranty offered may differ from market to market
-----------	--

Physical Controls:

Key 1 (favorite), Key 2,  
Key 3, Key 4, Key 5, Key  
6 (power)

On Screen Display:

Input Select, Audio  
Adjust, ViewMode, Color  
Adjust, Manual Image  
Adjust, Setup Menu

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.