



LCD DISPLAY

VX3219-2K-PRO-2

Key Features

- SuperClear® IPS panel ensures wide viewing angles and vibrant colors for immersive gaming
- A 165Hz refresh rate delivers fluid visuals for smoother gameplay
- Blazing-fast <0.5ms MPRT ensures razor-sharp visuals in fast-paced gaming
- AMD FreeSync™ Premium eliminates screen tearing and reduces screen stuttering
- HDR10 Delivers Stellar Contrast and Color Accuracy



Product Description

Experience immersive entertainment with the ViewSonic OMNI VX3219-2K-PRO-2 gaming monitor. Its high 165Hz refresh rate guarantees ultra-smooth animations, while the rapid <0.5 MPRT response time delivers smooth visuals and minimal input lag, making it perfect for fast-paced gaming. Featuring AMD FreeSync™ Premium to eliminate screen tearing and stuttering for seamless gaming experiences, this monitor also boasts ViewSonic's exclusive ViewMode™ presets, delivering stunning visuals optimized for heart-pounding gaming, captivating entertainment, creative editing, and beyond. The monitor is complete with versatile connectivity options, featuring DisplayPort and two HDMI inputs.

Visit Uswww.viewsonic.com

DISPLAY

Display Size (in.):	32
Viewable Area (in.):	31.5
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,200:1 (typ)
Dynamic Contrast Ratio:	50M:1
High Dynamic Range:	HDR10
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + FRC)
Aspect Ratio:	16:9
Response Time (MPRT):	0.43ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	165
Variable Refresh Rate Technology:	FreeSync Premium
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	DCI-P3: 95% coverage (Typ) NTSC: 97% size (Typ) sRGB: 137% size (Typ)
Pixel Size:	0.273 mm (H) x 0.273 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

CONNECTOR

3.5mm Audio Out:	1
HDMI 2.0 (with HDCP 2.2):	2
DisplayPort:	1
Power in:	DC Socket (Center Positive)

POWER

Eco Mode (Conserve):	37W
Eco Mode (optimized):	45W
Consumption (typical):	55W
Consumption (max):	57W
Voltage:	AC 100-240V
Stand-by:	0.5W

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	HDMI (v2.0): 24 ~ 222KHz, DisplayPort (v1.4): 24 ~ 250KHz
Frequency Vertical:	HDMI (v2.0): 48 ~ 144Hz, DisplayPort (v1.4): 48 ~ 165Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4)
---------------	------------------------------------------------

ERGONOMICS

Tilt (Forward/Back):	-5° / 20°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	17.4
Net Without Stand (lbs):	14.4
Gross (lbs):	23.1

WEIGHT (METRIC)

Net (kg):	7.9
Net Without Stand (kg):	6.6
Gross (kg):	10.5

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	37 x 21.1 x 6.3
Physical (in.):	28.1 x 20.6 x 9.3
Physical Without Stand (in.):	28.1 x 16.5 x 2.4

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	941 x 537 x 160
Physical (mm):	714 x 525 x 235
Physical Without Stand (mm):	714 x 420 x 61

GENERAL

Regulations:	RoHS, WEEE, BSMI, BIS, CCC, China RoHS, China Energy Label, CECP, China Environmental Label
PACKAGE CONTENTS:	VX3219-2K-PRO-2 x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.

Power Supply: External Power Adaptor

Warranty:

*Warranty offered may differ from market to market

ADDITIONAL HARDWARE

Kensington Lock Slot: 1

Cable Organization: Yes

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.