



LCD DISPLAY

VX3276-2K-mhd

Key Features

- SuperClear® IPS technology
- Frameless bezel and metallic triangle stand
- 10-bit colour
- HDMI, DisplayPort and mini DP inputs
- Dual integrated speakers



Product Description

The ViewSonic VX3276-2K-mhd is the perfect blend of style and performance with features that include a sizeable 32" panel, a minimalist design, and WQHD (2560 x 1440) resolution. The sleek design of an ultra-slim profile, metallic silver triangle stand, and a sleek edge-to-edge frameless bezel give the monitor a premium feel that fits nicely both at home and in the office. VX3276-2K-mhd features SuperClear® IPS technology and rich 10-bit colour to produce an extensive array of vibrant colours with wide viewing angles. Stereo sound is provided by the monitor's dual integrated speakers, while DisplayPort, Mini DisplayPort, and 2 HDMI ports offer flexible connectivity options for both general usage and gaming.

Visit Uswww.viewsonic.com

DISPLAY

Display Size (in.):	32
Viewable Area (in.):	31.5
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,200:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	75
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 102% size (Typ)
Pixel Size:	0.273 mm (H) x 0.273 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 7/8/8.1/10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

CONNECTOR

3.5mm Audio Out:	1
HDMI 1.4:	2
DisplayPort:	1
Mini DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

AUDIO

Internal Speakers:	2Watts x2
--------------------	-----------

POWER

Eco Mode (Conserve):	36W
Eco Mode (optimized):	41W
Consumption (typical):	43W
Consumption (max):	46W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

CONTROLS

Physical Controls:	Key 1 (game mode), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	HDMI (v1.4): 15 ~ 113KHz, DisplayPort (v1.2): 24 ~ 113KHz, mini DisplayPort (v1.2): 24 ~ 113KHz
Frequency Vertical:	HDMI (v1.4): 24 ~ 75Hz, DisplayPort (v1.2): 50 ~ 75Hz, mini DisplayPort (v1.2): 50 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), PCI-E - mini DisplayPort (v1.2)
---------------	---

ERGONOMICS

Tilt (Forward/Back):	-4° / 15°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	13.7
Net Without Stand (lbs):	12.3
Gross (lbs):	18.1

WEIGHT (METRIC)

Net (kg):	6.2
Net Without Stand (kg):	5.6
Gross (kg):	8.2

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	31.7 x 20 x 4.3
Physical (in.):	28.1 x 19.8 x 9.1
Physical Without Stand (in.):	28.1 x 16.4 x 1.5

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	806 x 509 x 109
Physical (mm):	713 x 504 x 230
Physical Without Stand (mm):	713 x 416 x 38

GENERAL

Regulations:	cTUVus, FCC-B, ICES003, Energy Star, CEC, MX-CoC, Mexico Energy, REACH, WEEE, BIS
PACKAGE CONTENTS:	VX3276-2K-MHD x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, Quick Start Guide x1

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.